



Tsunami Membrane Dryer System

P/N 21999-0357



- First-stage Tsunami™ Water Separator with Automatic Float Drain
- Second-stage Tsunami™ Oil Coalescer with Automatic Float Drain
- High Flow Piston Regulator Downstream

→ LOW MAINTENANCE

- Only second-stage coalescing element needs replacing
- No refrigerant to maintain
- No desiccants to replace
- No desiccant dust downstream

→ SPECIFICATIONS

- 15 CFM with 3.3 CFM sweep @ 100 PSI
- 175 PSI maximum inlet pressure
- 175°F maximum inlet temperature
- 1/2" NPT ports (3/8" and 1/4" bushing supplied)

→ EASY TO INSTALL

- No electrical connection
- Mount outside paint booth
- Comes pre-assembled

INLET PRESSURE	INLET TEMPERATURE	PRESSURE DEW POINT (RH%)	DEW POINT AT GUN PRESSURE SETTING		
			30 PSI	40 PSI	50 PSI
175	80°	17° (9)	-10° (2)	-7° (2)	-5° (3)
150	80°	22° (11)	-3° (3)	-1° (4)	3° (4)
100	80°	40° (24)	19° (9)	23° (11)	27° (14)

Tsunami Compressed Air Solutions™ is a division of



www.tsunami.us.com



Phone: 1- 800-782-5752 Fax: (763) 295-6601